

DS-2CE16C0T-IRF 1 MP Fixed Mini Bullet Camera



- HD 720p bullet camera
- Smart IR: up to 20 m IR distance
- Water and dust resistant (IP67)
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)

▪ Specification

| Camera | |
|------------------------|--|
| Image Sensor | 1 MP CMOS image sensor |
| Max. Resolution | 1280 (H) × 720 (V) |
| Min. Illumination | 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR |
| Shutter Time | PAL: 1/25 s to 1/50,000 s;NTSC: 1/30 s to 1/50,000 s |
| Day & Night | IR Cut Filter |
| Angle Adjustment | Pan: 0° to 360°, Tilt: 0° to 180°, Rotation: 0° to 360° |
| Signal System | PAL/NTSC |
| Lens | |
| Lens Type | 2.8 mm, 3.6 mm, 6 mm optional |
| Focal Length & FOV | Field of view: 70.9° (3.6 mm), 92° (2.8 mm), 56.7° (6 mm) |
| Lens Mount | M12 |
| Illuminator | |
| Supplement Light Type | IR |
| Supplement Light Range | Up to 20 m |
| Smart Supplement Light | Yes |
| Image | |
| Frame Rate | 720p@25fps/720p@30fps |
| SNR | >62 dB |
| Interface | |
| Video Output | Switchable TVI/AHD/CVI/CVBS,1 HD analog output |
| General | |
| Power | 12 V DC±15%, max. 4 W |
| Dimension | Φ 70 mm × 154.5 mm (2.76" × 6.08") |
| Weight | 400 g (0.88 lb.) |
| Operating Condition | -40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation) |
| Approval | |
| Protection | IP67 |

▪ Available Model

DS-2CE16COT-IRF(2.8mm)

DS-2CE16COT-IRF(3.6mm)

DS-2CE16COT-IRF(6mm)

- **Accessory**
- **Optional**

**DS-1280ZJ-XS
Junction Box**



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

